

DC BRUSHLESS FAN

REXNORD®

Model No.	Part Code	Bearing	Voltage	Current	Input Power	Speed	Air Flow	Static Pressure	Noise
REC		○ Sleeve ● Ball	VDC	A	W	RPM	CFM	mm H ₂ O	dB(A)

Plastic Housing With Plastic Impeller



2^{1/2}"

60 x 60 x 25 mm


6025 A12 W	DC051	○	12	0.10	1.2	3950	20	3.8	27
6025 A24 W	DC052	○	24	0.07	1.7	4200	20	3.8	27



3"

80 x 80 x 25 mm


8025 A12 W	DC081	○	12	0.13	1.6	2750	35	3.5	30
8025 B12 W	DC083	●	12	0.13	1.6	2850	35	3.5	30
8025 A24 W	DC082	○	24	0.09	2.2	2800	35	3.5	30
8025 B24 W	DC085	●	24	0.08	1.9	3000	35	3.5	30



3^{1/2}"

92 x 92 x 25 mm

9225 A12 W	DC111	○	12	0.14	1.7	2350	46	3.5	29
9225 A24 W	DC112	○	24	0.10	2.4	2500	46	3.5	29



4"

120 x 120 x 38 mm

Aluminium Housing With Plastic Impeller

12038 A12 W	DC151	○	12	0.40	4.8	3000	105	6.8	40
12038 B12 W	DC154	●	12	0.40	4.8	3050	116	6.8	40
12038 A24 W	DC152	○	24	0.17	4.0	2900	105	6.8	40
12038 B24 W	DC155	●	24	0.18	4.3	3000	116	6.8	40
12038 A48 W	DC153	○	48	0.13	6.2	3200	105	6.8	40
12038 B48 W	DC156	●	48	0.13	6.2	3250	116	6.8	40
12038 B48 H W	DC158	●	48	0.25	12	4250	164	9	52


* H - High Speed



6"

Ø172 x 150 x 51 mm

17251 B24 W	DC181	●	24	0.70	16.8	3400	300	20	55
17251 B48 W	DC182	●	48	0.35	16.8	3450	300	20	55



8"

Ø220 x 60 mm

22060 B24 W	DC201	●	24	1.00	24	2550	400	28	62
22060 B48 W	DC211	●	48	0.50	24	2600	400	28	62

Aluminium Housing With Metal Impeller



8"

225 x 225 x 80 mm

22580 B48 - MB	DC221	●	48	1.10	53	2750	647	24.6	67
----------------	-------	---	----	------	----	------	-----	------	----

10"

280 x 280 x 80 mm

28080 B48 - MB	DC251	●	48	1.85	89	2650	1200	30.6	69
----------------	-------	---	----	------	----	------	------	------	----